

Data Acquisition Modules

Distributed IO Modules



10:25:26 05/15/09 10:28:46 05/15/09 10:32:06 05/15/09 10:35:26 05/15/09 10:38:46 05/15/09 10:42:06 05/15/09 10:45:26 05/15/09 10:48:46 05/15/09 10:52:06 05/15/09 10:55:26 05/15/09

Tag5	953.9
Tag6	953.0
Tag7	953.9
Tag8	953.9
Tag9	953.9
Tag10	953.9
Tag11	953.9
Tag12	953.9



Features

- Portable
- Modbus connectivity
- Simple setup and easy handling
- Upto 127 Modules on RS485 network
- Isolated modules available for special applications
- Low-cost IO modules addition to existing PLC system
- LEDs for digital IO status, communication and power supply
- Standard software for module configuration and trouble shooting
- Data acquisition software for data storage and Real-time analysis on PC
- IO modules used with the third party softwares via Modbus RTU Protocol
- Interface with field devices to provide real-time data for SCADA/PLC/HMI
- Different types of IO Modules AI,AO,DI,DO,RTD,Thermocouples all available
- Direct reading of temperature without scaling by using RTD and Thermocouple Modules



IO Modules

A new line of Modbus based IO modules for data acquisition and other applications are available now. These IO modules offer good reliability, low-cost solution for distributed IO applications. They are portable, easy integrated with existing Modbus network, and simple to use for end users. Various types of IO modules are available for different kinds of requirements. All IO modules have LED indications for visualization of IO status (Digital) and fault diagnostic analysis. Some models with high isolation among inputs are also available for special applications. IO Studio software is used to setup communication of IO modules and checks the IO status in PC for diagnosis purpose. With Modbus RTU protocol, these IO modules configured as slaves will be easy to communicate with Modbus master such as SCADA/PLC/HMI. All IO modules have 2 wire RS485 interface with Modbus RTU Protocol.

Environmental & Physical

Communication

Approval Standards

Operating temperature	-10°C to +50°C	Interface	2 wire, RS485	Safety	IEC 950
Storage temperature	-40°C to +85°C	Modbus address setting	By Dip switch	EMC	IEC 61000-4-2-A1 Level 2
Dimension (WxHxD)	23 x 109 x 98mm	Modbus Max.address	127 only		IEC 61000-4-3-A1 Level 2
Weight	105 grams	Baud rate	2400, 4800, 9600, 19200,		IEC 61000-4-4 Level 3
Mounting	DIN Rail		38400, 57600, 115200		CISPR 11:1997-A1 /
		Parity	None, Even, Odd		EN 55011:1998
		Stop bits	1, 2		Group 1 Class A
		Data Bits	8		

Digital Modules



IO-16DI



IO-16DO



IO-4RO



IO-8DIO

Specifications

Digital Inputs	16	N.A	N.A	8
No.of Counters	16	N.A	N.A	8
Counter Resolution	32 Bit	N.A	N.A	32 Bit
Counter frequency	1 KHz	N.A	N.A	1 KHz
Counter Mode	UP/Down	N.A	N.A	UP/Down
Pulse width	Minimum 500 Micro sec	N.A	N.A	Minimum 500 Micro sec
Input Impedance	2200 ohms	N.A	N.A	2200 ohms
Isolation (Field&Logic)	1500 V RMS	N.A	N.A	1500 V RMS
Status Indication	LED for each channel	N.A	N.A	LED for each channel
Digital Outputs	0	16	4	8
Type of Digital output	N A .	Open collector	Relay, Form C	Open collector
Maximum load current	N A .	100 mA/channel	0.5A / 1 A each ch.	100 mA/channel
Maximum load Voltage	N.A	36 V DC	220 V AC/ 28 V DC	36 V DC
Isolation (Field&Logic)	N A .	1500 V RMS	1000 V RMS	1500 V RMS
Status Indication	N.A	LED for each channel	LED for each channel	LED for each channel
Power supply	12 to 24 V DC	12 to 24 V DC	24 V DC	12 to 24 V DC

Combination Module

Specifications

Analog Inputs	2	0-20 mA/0-10 V DC, Resolution: 12 bit, I/P Impedance: 250 Ohms for current I/P, 190 K Ohms for Voltage I/P
Analog Outputs	1	0(4)-20 mA/0(2)-10 V DC, Resolution: 12 bit, Drift: 100 PPM/Deg.C, Accuracy: 0.05 % of span, Load: 1000 ohms @ 24 V for Current, 2000 Ohms for voltage output.
Digital Inputs	4	Counter, 32 bit, Frequency: 50 Hz, Pulse width: 20 ms, Voltage:10-26 V DC
Digital Outputs	2	Open collector, 36 V DC (Max), 100 mA/Output
RTD Inputs	2	Connection:2/3 wire, Types: PT100/Ni120/PT1000, Resolution: 0.1 deg.C, Isolation: 1500 V RMS
Power supply		12 V to 24 V DC

IO-DAIO



*For IO-DAIO module, LED is available for power on and communication status only.

Analog Modules RTD and Thermocouple Inputs

IO-6RTD



IO-8TC



IO-8TCS



Specifications

Input	6, RTD Inputs	8, Thermocouple Inputs	8, Isolated Thermocouple Inputs
Type	PT100, Ni 120, PT1000, Ni1000 -DIN, NI1000 Landys & Gyr 10-400 Ohms, 100-4000 Ohms	J,K,E,T,N,B,S,R,mV,C,D and G	J,K,E,T,N,B,S,R,mV,C,D and G
Connection	2/3 wire	2 wire	2 wire
Resolution	0.1 Deg.C	0.1 Deg.C	0.1 Deg.C
Sample rate	31 samples/ min	42 samples/ min	37 samples/ min
Drift	100 PPM/Deg.C	100 PPM/Deg.C	100 PPM/Deg.C
Isolation (Field&Logic)	1500 V RMS	1500 V RMS	1500 V RMS 350 V (P-P) between channels
Power supply	12 V to 24 V DC	12 V to 24 V DC	12 V to 24 V DC

Current & Voltage Inputs

IO-8AI



IO-8AIV



IO-8AIIS



IO-8AIVS



Specifications

Analog Inputs	8	8	8	8
Type	Single-Ended	Single-Ended	Differential	Differential
Voltage	N.A	0 - 10 V DC/ 0 - 5V DC	N.A	0(2) - 10 V / 0(1) - 5V DC
Current	0-20 mA	N.A	0-20 mA	N.A
Offset by switch	4 mA	2 V DC (0-10)/ 1 V DC(0-5)	4 mA	2 V DC (0-10)/ 1 V DC(0-5)
Sample rate	12.5 samples/sec	12.5 samples/sec	12.5 samples/sec	12.5 samples/sec
I/P Impedance	250 Ohms	20 K Ohms	250 Ohms	110 Kohms
Isolation(Ch-Ch)	N.A	N.A	350 V (P-P)	350 V (P-P)
Drift	50 ppm/deg.C	50 ppm/deg.C	100 ppm/deg.C	100 ppm/deg.C
Accuracy	0.2 % of span	0.2 % of span	0.2 % of span	0.2 % of span
Isolation (Field&Logic)	1500 V RMS	1500 V RMS	1000 V RMS	1500 V RMS
Power supply	12 V to 24 V DC	12 V to 24 V DC	12 V to 24 V DC	12 V to 24 V DC

Analog Outputs

Specifications

IO-8AOI

IO-8AOV

Analog Outputs	8	8
Voltage	N.A	0-10V DC
Current	0-20 mA	N.A
Offset	4 mA	2 V DC
Resolution	12 bits (0-4095)	12 bits (0-4095)
Drift	100 ppm/deg.C	100 ppm/deg.C
Accuracy	0.05 % of span	0.05 % of span
Load	1000 Ohms @ 24 V DC	2000 Ohms
Isolation (Field&Logic)	1500 V RMS	1500 V RMS
Power supply	12 V to 24 V DC	12 V to 24 V DC

IO-8AOI



IO-8AOV

